

Drum Mount Fogger

Drum Mount Foggers are designed for users with larger fogging requirements and provide a complete system that is cost effective and reliable solution when treating large areas for a long period of time.

Foggers can be controlled by hand or on a timer and since the chemical drum serves as an ample reservoir, Drum Mount units require little attention.



Applications

- Waste Treatment Plants
- Warehouses
- Food Processing Plants
- Barns
- Dairies



The 672 Drum Mount includes a one-turn control valve to allow you to adjust liquid output (0-300 ml/min) and droplet size (intermediate fog to heavy wet fog). Higher flows produce larger droplets.

The 672DM is a 'cold' fogger and is suitable for use with both water and oil-based liquids. The 672DM uses shear turbulence to provide a 'tornado' effect at the nozzle. This method enables the fog to reach up to 30 feet directionally in still air!

SPECIFICATION

Motor	240V (4.0 amp) or 110V (8.0amp) Motor saver brushes protect commutator when worn but allow continuous operation
Particle Size	15-30 micron (Adjustable)
Chemicals	Suitable for water and oil-based solutions
Liquid Flow Rate	0-300 ml/min adjustable with one-turn valve
Capacity	Mounts to a variety of chemical drums (2" NPT as standard – adaptors available)
Materials of Construction	Power head, drum adapter - aluminum Tubing - fuel and oil resistant vinyl Fittings and control valve - brass
Dimensions	H x L x Dia: 39 x 32 x 22 cm